

12K TWO-POST EQ12

This lift features 2-Stage front and rear arms with automatic arm restraints for safe spotting, a single-point lock release system, a padded overhead shut-off bar to prevent vehicle damage, and a black textured powder coat finish for sleek, long-lasting durability.



REQUIREMENTS

HEIGHT: 13' 11" / 14' 7" MINIMUM

WIDTH: 14' RECOMMENDED

DEPTH: 24' RECOMMENDED

POWER: 208-230V, 1PH, 30A

CONCRETE
4" thick, reinforced, free from cracks/seams,
3500+ psi & cured 28+ days

SPECIFICATIONS

MODEL NUMBER	EQ12
Lifting Capacity	12,000 lbs.
Configuration	Symmetric
Arms	2-Stage Front & Rear
Overall Height	166" / 175"
Rise Height	75 ¹⁵ / ₁₆ "
Pad Height	4 ⁷ / ₈ "
Overall Width (C)	11' 7 ³ / ₄ "
Inside Columns (D)	9' 7"
Drive-Thru Clearance	103"
Floor to Overhead Switch	13' 3 ¹ / ₂ "
Front Arm Reach (G)	35 ³ / ₄ " - 54 ¹ / ₂ "
Rear Arm Reach (F)	35 ³ / ₄ " - 54 ¹ / ₂ "
Motor / Voltage	2HP, 208-230v, 60Hz, 1Ph
Rise Time	61 s
Ceiling Height Req.	Min. 13' 11" / 14' 7"
ALI® Certified	Yes
Color	Black

SERVICE BAY LAYOUT

